

DGS-1 single shielded (6000x)

Industrial standard high quality unbalanced audio cable with noise protecting conductive plastic layer (3) to eliminate microphonics caused by mechanical movement of the cable.

Single Reussen shield giving accurate shielding for standard usage. Refer to page 3 and consider our double-shielded cable GAC-1 for same application and usages.

Check our OEM prices and special branded productions just for you!
Limited availability! Minimum order can apply!



1	Jacket	PVC, \varnothing 6.0 mm, max.
2	Shield	Bare copper wires (0.10 mm), 100% coverage
3	Layer	PVC, conductive
4	Insulation	PE, \varnothing 1.48 mm
5	Conductor	Stranded bare copper wires, 7 x 0.20 mm (0.22 mm ²)

Conductor resistance	< 85 Ohm /km	Test voltage cond/cond	500 V eff.
Shielding resistance	< 40 Ohm /km	Test voltage cond/shield	1000 V eff.
Insulation resistance	> 1G Ohm /km		
Capacitance	< 111 nF /km	Temperature range (flex)	- 5° to +50° C
		Temperature range (fix)	-30° to +70° C

Order No.	Type	\varnothing mm	Color	Spool Size	Weight /Spool	Shipping Unit
60001	DGS-1	6.0	red	100 m	4.5 kg	4 x 100 m
60004	DGS-1	6.0	blue	100 m	4.5 kg	4 x 100 m
60005	DGS-1	6.0	yellow	100 m	4.5 kg	4 x 100 m
60008	DGS-1	6.0	black	100 m	4.5 kg	4 x 100 m

Contact us for availability. Limited stock on hand. This is not a standard stocked product. Minimum orders can apply

the world wide best choice in professional wiring

construction

specifications

ordering data