
Balanced double shielded audio cable! Special version of our popular double shielded microphone cable GAC-2, with an additional polyurethan (PUR) jacket.

This is the most reliable and strongest microphone cable available in the market.

Similar versions available with extra low noise (10421) with conductive separation tube for minimal handling noise for film microphone booms and as industrial standard cable for a lower price (10405)...



1	Jacket	PUR, ø 5.4 mm, blue	tion
2	Separation	PVC, ø 4.4 mm, white	_ ട്
3	Shield No. 1	Bare copper wires (0.10 mm), 100% coverage	<u>st</u>
4	Shield No. 2	Bare copper wires (0.10 mm), 100% coverage	_ 5
5	Separation	PVC, ø 3.1 mm, white	_ 0
6	Insulation	PVC, white and brown Ø 1.2 mm, wrapped	_
7	Conductor	Stranded bare copper wires, 48 x 0.07 mm (0.19 mm²)	

Conductor resistance	< 90 Ohm /km	Test voltage cond/cond	500 V eff.
Shielding resistance	< 20 Ohm /km	Test voltage cond/shield	2000 V eff.
Capacitance cond/cond	< 86 nF /km	Operating voltage	low voltage
Capacitance cond/shield	< 146 nF /km	Temperature range (flex)	- 5° to +50° C
		Temperature range (fix)	-30° to +70° C

Order No.	Туре	ø mm	Color	Spool Size	Weight /Spool	Shipping Unit
10502	GAC-2 PUR	5.4	blue	100 m	4.50 kg	4 x 100 m